



NATURAL GAS VEHICLE COOPERATIVE PURCHASING PROGRAM
CNG Conversion Specs for Vehicle Configuration No. 14:
Ford F-350 Pickup, Cab & Chassis

DEALER NAME _____ **BID AMOUNT** _____

Mark "S" for standard,
or specify deviations.

- | | | |
|-------------------|---|--|
| 1) Make/Model | A) Cab & Chassis, Pick Up. Specify Year: _____
B) Make: _____ & Model _____ | A. _____
B. _____ |
| 2) Rating | A) G.V.W.: 10,001 lbs Minimum, Show GVW _____
B) Payload: 2,845 lbs Minimum, Show Payload _____ | A. _____
B. _____ |
| 3) Dimensions | A) Wheelbase: 140.8" ± 3", Show Wheelbase _____
B) .C.A.: 60" ± 1", Specify CA: _____ | A. _____
B. _____ |
| 4) Engine | A) 5.4 L, EFI, V8, Dedicated Compressed Natural Gas
B) Show Engine C.I.D. or Liters _____
C) Gaseous Prep Engine | A. _____
B. _____
C. _____ |
| 5) Cooling System | A) Maximum Capacity Cooling Available With Coolant Recovery System | A. _____ |
| 6) Air Cond. | A) Factory Installed With Integral Heater & Defroster | A. _____ |
| 7) Electrical | A) Battery: 12 Volt, At Least 650 CCA
B) Alternator: 12 Volt, At Least 130 AMP
C) Dual Note Electric Horns (<u>No Exceptions</u>)
D) Cab Or Roof Mounted Center High Mount Stop Light
E) Heavy Duty Signal And Emergency Flashers | A. _____
B. _____
C. _____
D. _____
E. _____ |
| 8) Radio | A) AM/FM Stereo Radio With Manual Antenna | A. _____ |
| 9) Fuel System | A) CNG Cylinder 2.5 GGE Minimum. 3600 psi.
Mounted Between Frame Rails And Shielded. Specify Capacity: _____ | A. _____ |



- 10)Interior
 - A) Air Bag Supplemental System: Driver-Side
 - B) Dome Light In Cab
 - C) 12 Volt Power Outlet Dash Mounted
 - D) Seat Belts: Lap and Shoulder
 - E) Gauges: Oil Pressure, Temperature, Voltmeter, Fuel & Speedometer
 - F) Mirror: Inside Rear View, Day And Night
 - G) Sun Visors: Right And Left Side
 - H) Seat: 40-20-40 Split-Bench
 - I) Vinyl Upholstery: Grey or Charcoal Color
Show Color _____
 - J) Full Floor Mat: Black Rubber
 - K) Arm Rests: Right And Left Side Doors

- 11)Exterior
 - A) Cab: Conventional
 - B) Frame: Standard
 - C) Mirrors: Dual Manual, 6" x 9" ± 1" Low Mount, Black
With Convex Right Side Mirror
 - D) Windows: Tinted Glass All Around
 - E) Wipers: 2 Speed Intermittent With Washers

- 12)Axles
 - A) Front: 3,700 lbs Minimum, Show Capacity _____
 - B) Rear: 5,300 lbs Minimum, Show Capacity _____

- 13)Ratio
 - A) Show Standard Ratio For Powertrain .

- 14)Springs
 - A) Front: 3,100 lbs Minimum, Show Capacity _____
 - B) Rear: 4,800 lbs Minimum, Show Capacity _____
 - C) Stabilizer Bar: Front

- 15)Shocks
 - A) Heavy Duty Front And Rear

- 16)Brakes
 - A) Power Assist with Four-Wheel Anti-Lock
 - B) Front: Disc
 - C) Rear: Drum

- 17)Transmission
 - A) 4 Speed Automatic Overdrive With Auxiliary Oil To Air Cooler
 - B) Column Mounted Transmission Shift Selector

- 18)Steering
 - A) Power

- 19)Tires
 - A) 5 Each: LT245/75R16-E, SBR-BSW, All-Season Tread

- 20)Wheels
 - A) 5 Each: Steel 16.0" x 7.0"

