



NATURAL GAS VEHICLE COOPERATIVE PURCHASING PROGRAM
CNG Conversion Specs for Vehicle Configuration No. 15:
Chevrolet/GMC 2500 Pickup (4x2) – 8’ bed

DEALER NAME _____ **BID AMOUNT** _____

Mark "S" for standard,
or specify deviations.

- | | | |
|------------------|--|--|
| 1)Make/Model | A) Heavy Duty Pickup, 8' Bed, <u>GMC or Chevrolet 2500</u>
B) Show Make _____ Model _____ | A. _____
B. _____ |
| 2)Rating | A) G.V.W.: 9,200 lbs, Show GVW _____
B) Payload: 2,500 lbs, Show Payload _____ | A. _____
B. _____ |
| 3)Dimensions | A) Wheelbase: 133", Show Wheelbase _____
B) Pickup Box: 8 Foot Length | A. _____
B. _____ |
| 4)Engine | A) <u>Natural Gas Dedicated:</u> 6.0 Liter, V8
B) Show Engine C.I.D. or Liters _____ | A. _____
B. _____ |
| 5)Cooling System | A) Maximum Capacity Cooling Available With Coolant Recovery System | A. _____ |
| 6)Air Cond. | A) Factory Installed With Integral Heater & Defroster | A. _____ |
| 7)Electrical | A) Battery: 12 Volt, 600 CCA
B) Alternator: 12 Volt, 100 AMP
C) Dual Note Electric Horns
D) Roof Mounted Center High Mount Stop Light | A. _____
B. _____
C. _____
D. _____ |
| 8)Radio | A) AM/FM Stereo Radio With Manual Antenna | A. _____ |
| 9)Fuel System | A) CNG Cylinder 21 GGE Minimum. 3600 psi.
In The Bed Mounted And Shielded. Specify Capacity: _____ | A. _____ |



- 10) Interior
 - A) Dome Light In Cab
 - B) 12 Volt Power Outlet Dash Mounted
 - C) Seat Belts: Lap and Shoulder
 - D) Gauges: Oil Pressure, Temperature, Ammeter, Speedometer
And Natural Gas Pressure
 - E) Mirror: Inside Rear View, Day And Night
 - F) Sun Visors: Right And Left Side
 - G) Seat: 40-20-40 Split-Bench
 - H) Upholstery: Vinyl, Blue Color
 - I) Full Floor Mat: Black Rubber
 - J) Arm Rests: Right And Left Side Doors

- 11)Exterior
 - A) Cab: Conventional
 - B) Frame: Standard
 - C) Mirrors: Dual Manual, 6.5" x 9" Low Mount, Black,
With Convex Right Side Mirror
 - D) Windows: Tinted Glass All Around
 - E) Wipers: Two Speed Intermittent With Washers

- 12)Axles
 - A) Front: 3,300 lbs Minimum, Show Capacity _____
 - B) Rear: 4,800 lbs Minimum, Show Capacity _____

- 13)Ratio
 - A) Show Standard Ratio For Powertrain _____

- 14)Springs
 - A) Front: 3,300 lbs Minimum, Show Capacity _____
 - B) Rear: 4,800 lbs Minimum, Show Capacity _____
 - C) Stabilizer Bar: Front

- 15)Shocks
 - A) Heavy Duty Front And Rear

- 16)Brakes
 - A) Power Assist with Four-Wheel Anti-Lock
 - B) Front: Disc
 - C) Rear: Drum

- 17)Transmission
 - A) 6 Speed Automatic Overdrive With Auxiliary Transmission Oil Cooler
 - B) Column Mounted Transmission Shift Selector

- 18)Steering
 - A) Power

- 19)Tires
 - A) 5 Each: LT245/75R16-E, SBR-BSW, All-Season Tread

- 20)Wheels
 - A) 5 Each: 16.0 x 6.5 DC, To Match Tires
 - B) 5 Each: Trim Rings & Hub Caps

- 21)Spare
 - A) Full Size Mounted Under Bed

